



## OSD 225



### MaxFlex OIL SUCTION AND DELIVERY HOSE 225 PSI

Tank truck and tank wagon suction and delivery hose; it withstands the full vacuum; used for a wide range of petroleum products up to 50% aromatic content.

- TEMPERATURE RANGE** : -40°C to +100°C
- CONSTRUCTION TUBE** : Black, smooth, nitrile compound
- REINFORCEMENT** : High strength synthetic cord plus helix and anti-static copper wire
- COVER** : Black, smooth (wrapped finish) high grade chloroprene rubber, compounded for an excellent resistant to weather, ozone abrasion and oil
- COLLS** : 61 meter (200ft) continuous length; other length available on request

PART NO	I.D.		O.D.		WORKING PRESSURE		BURSTING PRESSURE		WEIGHT (normal)	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft
OSD225-0200	51	2	62	2-13/32	15	225	45	675	1.81	1.24
OSD225-0250	63	2-1/2	77	3-1/32	15	225	45	675	2.78	1.56
OSD225-0300	76	3	92	3-5/8	15	225	45	675	2.93	2.01
OSD225-0350	90	3-1/2	104	4-3/32	15	225	45	675	3.46	2.37
OSD225-0400	102	4	120	4-47/64	15	225	45	675	4.95	3.36
OSD225-0500	127	5	147	5-51/64	15	225	45	675	6.60	9.64
OSD225-0600	152	6	172	6-25/32	15	225	45	675	7.80	11.39
OSD225-0800	203	8	227	8-15/16	15	225	45	675	9.00	13.14

\*Other size, pressure rating and colours available on request