



OSD 300



MaxFlex OIL SUCTION AND DELIVERY HOSE 300 PSI

Heavy duty suction and delivery hose, excellent for use as a tank truck or tank wagon hose, it withstand the full vacuum, its antistatic cover conforms fully to PTB specification, used for a wide range of petroleum products up to 50% aromatic content.

- TEMPERATURE RANGE** : -40°C to +100°C
- CONSTRUCTION TUBE** : Black, smooth, nitrile compound
- REINFORCEMENT** : High tensile textile cords with embedded steel helix wires
- COVER** : Black, smooth (wrapped finish) high grade chloropene rubber, compounded for an excellent resistance to weather, ozone, abrasion and oil resistant, antistatic
- COLLS** : 61 meter (200ft) continuous length; other length available on request
- SAFETY** : 4: 1

PART NO	I.D.		O.D.		WORKING PRESSURE		BURSTING PRESSURE		WEIGHT (normal)
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m
OSD300-0051	51	2	65	2-9/16	20	300	80	1200	1.81
OSD300-0063	63	2-1/2	80	3-3/16	20	300	80	1200	2.78
OSD300-0076	76	3	93	3-21/32	20	300	80	1200	2.93
OSD300-0102	102	4	120	4-47/64	20	300	80	1200	4.95
OSD300-0127	127	5	149	5-7/8	20	300	80	1200	6.60
OSD300-0152	152	6	174	6-55/65	20	300	80	1200	7.80

*Other size, pressure rating and colours available on request