



FLT ENGINEERING SDN. BHD.

WSD 150



MaxFlex WATER SUCTION OR DISCHARGE HOSE 150PSI

Mandrel built heavy water suction & discharge hose, it handles sewage, waste water, mud, etc

TEMPERATURE RANGE : -40°C to +85°C

CONSTRUCTION:
TUBE

: Black, smooth, synthetic rubber resistant to water with ph value 5 to 8

REINFORCEMENT

: High strength synthetic cord plus helix

COVER

: Black, smooth (wrapped finish) synthetic rubber, abrasion and weathering

COLLS

: 61 meter (200ft) continuous length; other length available on request

PART NO	I.D.		O.D.		WORKING PRESSURE	BURSTING PRESSURE	WEIGHT (normal)
	mm	inch	mm	inch			
WSDH150-0125	32	1-1/4	43	1-21/32	10	30	0.97
WSDH150-0150	38	1-1/2	50	1-15/16	10	30	1.27
WSDH150-0200	51	2	1863	2-15/32	10	30	1.72
WSDH150-0250	63	2-1/2	77	3-1/32	10	30	2.37
WSDH150-0300	76	3	89	3-1/2	10	30	2.79
WSDH150-0350	90	3-1/2	103	4-1/32	10	30	3.86
WSDH150-0338	86	3-3/8	99	3-29/32	10	30	3.80
WSDH150-0400	102	4	118	4-9/16	10	30	4.33
WSDH150-0450	115	4-1/2	132	5-13/64	10	30	5.20
WSDH150-0500	127	5	144	5-5/8	10	30	7.23
WSDH150-0600	152	6	171	6-3/4	10	30	10.18
WSDH150-0800	203	8	227	8-15/16	10	30	14.80
WSDH150-1000	254	10	280	11-1/8	10	30	16.34
WSDH150-1000	305	12	336	13-15/64	10	30	24.63

*Other size, pressure rating and colours available on request