



WSD 300



MaxFlex WATER SUCTION OR DISCHARGE HOSE 300PSI

Mandrel built heavy water suction & discharge hose, it handles sewage, waste water, mud, etc

TEMPERATURE RANGE : -40°C to +85°C

CONSTRUCTION:

TUBE : Black, smooth, synthetic rubber resistant to water with ph value 5 to 8

REINFORCEMENT : High strength synthetic cord plus helix

COVER : Black, smooth (wrapped finish) synthetic rubber, abrasion and weathering

COLLS : 61 meter (200ft) continuous length; other length available on request

SAFETY : 4:1

PART NO	I.D.		O.D.		WORKING PRESSURE	BURSTING PRESSURE	WEIGHT (normal)
	mm	inch	mm	inch			
WSD300-0032	32	1-1/4	43	1-21/32	20	80	0.97
WSD300-0038	38	1-1/2	50	1-15/16	20	80	1.27
WSD300-0051	51	2	63	2-15/32	20	80	1.72
WSD300-0063	63	2-1/2	77	3-1/32	20	80	2.37
WSD300-0076	76	3	89	3-1/2	20	80	2.79
WSD300-0090	90	3-1/2	103	4-1/32	20	80	3.86
WSD300-0086	86	3-3/8	99	3-29/32	20	80	3.80
WSD300-0102	102	4	118	4-9/16	20	80	4.33
WSD300-0115	115	4-1/2	132	5-13/64	20	80	5.20
WSD300-0127	127	5	144	5-5/8	20	80	7.23
WSD300-0152	152	6	171	6-3/4	20	80	10.18

*Other size, pressure rating and colours available on request