

MAXIFLEX[®] XLPE-10 BAR



ACID AND CHEMICAL SUCTION & DELIVERY 10 BAR (150 PSI) – XLPE

TUBE	: Transparent Conductive XLPE (CROSS LINKED POLYETHEYLENE)
TEMPERATURE RANGE	: -40°C to +100°C
REINFORCEMENT	: High tensile textile cords with embedded steel helix wires
COVER	: Green EPDM- Abrasion, ozone and weather resistant
APPLICATION	: Acid and chemical suction and delivery. Suitable for 90% existing chemicals
BRAND TYPE	: MAXIFLEX [®] XLPE
SAFETY FACTOR	: 4:1

PART NO	I.D.	O.D.	WORKING PRESSURE	BURSTING PRESSURE	WEIGHT (nominal)
	mm	mm	bar	bar	g/m
XLPE150-0075	19	32	10	40	705
XLPE150-0100	25	37	10	40	850
XLPE150-0125	32	44	10	40	1020
XLPE150-0150	38	51	10	40	1170
XLPE150-0200	51	65	10	40	1530
XLPE150-0250	63	79	10	40	2320
XLPE150-0300	76	92	10	40	2780
XLPE150-0400	102	118	10	40	3790

* Other size, pressure rating and colours available on request

* Fire Retardant Certified as per DIN EN ISO 15540 available upon request, model XLPE 150 – FD.